


REDUCERS


Elongated
For butt welding
Tekwelding
IR-welding
BCF-welding



d ₁ /d ₂ (mm)	l ₁ (mm)	l ₂ (mm)	L (mm)	PN10	
				S/S (mm)	Weight (kg/pc.)
25/20	39	40	85	1.9/1.9	0.021
32/20	44	40	95	2.4/1.9	0.034
32/25	44	40	95	2.4/1.9	0.035
40/20	49	40	105	2.4/1.9	0.042
40/25	49	40	104	2.4/1.9	0.044
40/32	50	44	105	2.4/2.4	0.050
50/25	56	40	120	3.0/1.9	0.071
50/32	59	45	122	3.0/2.4	0.080
50/40	57	49	126	3.0/2.4	0.087
63/32	64	47	135	3.0/2.4	0.110
63/40	60	48	130	3.0/2.4	0.111
63/50	66	60	153	3.0/3.0	0.146
75/50	63	57	148	3.6/3.0	0.180
75/63	65	57	149	3.6/3.0	0.201
90/63	70	59	160	4.3/3.0	0.259
90/75	75	62	162	4.3/3.6	0.316
110/63	83	57	180	5.3/3.0	0.424
110/90	79	72	180	5.3/4.3	0.504
140/110	42	38	106	6.7/5.3	0.470
160/110	98	88	224	7.7/5.3	1.300

REDUCERS

PN 20
for socket welding



D ₁ /D ₂ (mm)	dsp (mm)	L (mm)	k (mm)	P (mm)	Weight (kg/pc.)
20/16	24	35	20.5	14.5	0.014
25/16	24	40	25.5	14.5	0.020
25/20	29	40	24.5	15.5	0.022
32/20	29	44	28.5	15.5	0.031
32/25	35	44	26.5	17.5	0.035
40/20	29	49	33.5	15.5	0.03
40/25	35	49	31.5	17.5	0.046
40/32	43	49	29.5	19.5	0.054
50/20	29	55	39.5	15.5	0.064
50/25	35	55	37.5	17.5	0.067
50/32	43	55	35.5	19.5	0.073
50/40	52	55	33.5	21.5	0.089
63/25	35	64	46.5	17.5	0.107
63/32	43	64	44.5	19.5	0.111
63/40	52	64	42.5	21.5	0.126
63/50	64	64	40.5	23.5	0.149
75/63	81	64	36.0	28.0	0.205
90/63	81	87	59.0	28.0	0.353
90/75	92	87	54.5	32.5	0.369
110/63	81	87	59.0	28.0	0.467
110/90	113	87	50.5	36.5	0.575

